

# Visage Series

IN-CEILING SPEAKERS



*RBH's Visage Series speakers deliver the finest performance and detail while being visually inconspicuous.*

*Visage Series in-ceiling speakers come with round, edge-to-edge magnetic grilles, but square grilles are also available separately. Grille cut-away shown to highlight speaker detail.*



REDEFINING THE WAY YOU EXPERIENCE SOUND.™

# Visage Series In-ceiling Speakers

The Visage Series in-ceiling speakers are designed for those who are just as fussy with the appearance of their home audio as they are about the sound quality. The easy-to-install, micro-perforated magnetic grilles cover and protect the speakers, providing a very attractive alternative to typical frame-type in-ceiling speaker designs. The Visage Series grilles can also be painted to allow the speakers to virtually hide in the ceiling, yet still deliver the exceptional sound RBH speakers are known for. Bringing together our most popular in-ceiling speaker models with the elegance of a contemporary frameless design, the Visage Series embodies RBH Sound's dedication to pleasing our listeners.



**RBH SOUND**

382 Marshall Way, Ste. A  
 Layton, Utah, USA 84041  
 Toll Free: (800) 543-2205  
 Fax: (801) 543-3300  
<http://rbhsound.com>

## VA-607 In-ceiling 2-way Speaker



**Frequency Response:** 55Hz-20kHz (±3dB)  
**Sensitivity:** 90dB (2.83V @ 1 Meter)  
**Recommended Power:** 10-80 Watts  
**Drive Units:** (1) 6-1/2" (165mm) Poly Graphite Cone Woofer  
 (1) 1" (25mm) Silk Dome Tweeter  
**Cutout Dimensions:** 7-3/4" (197mm) Dia.  
**Finished Dimensions:** 8-3/4" Dia. x 3-7/8" D (227mm Dia. x 104mm D)  
**Weight:** 2.5 lbs. (1.13 kg)

## VA-615 In-ceiling 2-way Speaker



**Frequency Response:** 55Hz-20kHz (±3dB)  
**Sensitivity:** 90dB (2.83V @ 1 Meter)  
**Recommended Power:** 10-80 Watts  
**Drive Units:** (1) 6-1/2" (165mm) Poly Graphite Cone Woofer  
 (1) 1" (25mm) Silk Dome Tweeter  
**Cutout Dimensions:** 7-3/4" (197mm) Dia.  
**Finished Dimensions:** 9" Dia. x 3-7/8" D (227mm Dia. x 98mm D)  
**Weight:** 3.45 lbs. (1.56 kg)

## VA-615DS In-ceiling 2-way Dual Channel Speaker



**Frequency Response:** 55Hz-20kHz (±3dB)  
**Sensitivity:** 90dB (2.83V @ 1 Meter)  
**Recommended Power:** 10-80 Watts  
**Drive Units:** (1) 6-1/2" (165mm) Poly Graphite Cone Woofer  
 (2) 3/4" (25mm) Silk Dome Tweeter  
**Cutout Dimensions:** 7-3/4" (197mm) Dia.  
**Finished Dimensions:** 9" Dia. x 3-7/8" D (227mm Dia. x 98mm D)  
**Weight:** 3.45 lbs. (1.56 kg)

## VF-615 In-ceiling 2-way Speaker



**Frequency Response:** 50Hz-20kHz (±3dB)  
**Sensitivity:** 90dB (2.83V @ 1 Meter)  
**Recommended Power:** 15-100 Watts  
**Drive Units:** (1) 6-1/2" (165mm) Fiberglass Matrix Cone Woofer  
 (1) 1" (25mm) Aluminum Dome Tweeter  
**Cutout Dimensions:** 7-3/4" (197mm) Dia.  
**Finished Dimensions:** 9" Dia. x 4-3/8" D (227mm Dia. x 111mm D)  
**Weight:** 3.8 lbs. (1.72 kg)

## VM-615 In-ceiling 2-way Speaker



**Frequency Response:** 55Hz-20kHz (±3dB)  
**Sensitivity:** 90dB (2.83V @ 1 Meter)  
**Recommended Power:** 10-80 Watts  
**Drive Units:** (1) 6-1/2" (165mm) Aluminum Cone Woofer  
 (1) 1" (25mm) Aluminum Dome Tweeter  
**Cutout Dimensions:** 7-3/4" (197mm) Dia.  
**Finished Dimensions:** 9" Dia. x 4-3/8" D (227mm Dia. x 111mm D)  
**Weight:** 5.85 lbs. (2.65 kg)

## VA-615L In-ceiling LCR Speaker



**Frequency Response:** 55Hz-20kHz (±3dB)  
**Sensitivity:** 90dB (2.83V @ 1 Meter)  
**Recommended Power:** 10-80 Watts  
**Drive Units:**  
 (1) 6-1/2" (165mm) Poly Graphite Cone Woofer  
 (1) 1" (25mm) Silk Dome Tweeter  
**Cutout Dimensions:** 7-3/4" (197mm) Dia.  
**Finished Dimensions:** 9-1/8" Dia. x 4-3/4" D  
 (232mm Dia. x 121mm D)  
**Weight:** 3.45 lbs. (1.59 kg)

## VM-615L In-ceiling LCR Speaker



**Frequency Response:** 50Hz-20kHz (±3dB)  
**Sensitivity:** 88dB (2.83V @ 1 Meter)  
**Recommended Power:** 15-120 Watts  
**Drive Units:**  
 (1) 6-1/2" (165mm) Aluminum Cone Woofer  
 (1) 1" (25mm) Aluminum Dome Tweeter  
**Cutout Dimensions:** 8-1/4" (210mm) Dia.  
**Finished Dimensions:** 9-3/8" Dia. x 4-3/4" D  
 (238mm Dia. x 121mm D)  
**Weight:** 3.7 lbs. (1.68 kg)

## VA-815 In-ceiling 2-way Speaker



**Frequency Response:** 50Hz-20kHz (±3dB)  
**Sensitivity:** 92dB (2.83V @ 1 Meter)  
**Recommended Power:** 10-100 Watts  
**Drive Units:**  
 (1) 8" (203mm) Poly Graphite Cone Woofer  
 (1) 1" (25mm) Silk Dome Tweeter  
**Cutout Dimensions:** 9-3/4" (197mm) Dia.  
**Finished Dimensions:**  
 10-3/4" Dia. x 4-3/4" D (271mm Dia. x 121mm D)  
**Weight:** 5 lbs. (2.27 kg)

## VA-815L In-ceiling LCR Speaker



**Frequency Response:** 50Hz-20kHz (±3dB)  
**Sensitivity:** 92dB (2.83V @ 1 Meter)  
**Recommended Power:** 10-100 Watts  
**Drive Units:**  
 (1) 8" (203mm) Poly Graphite Cone Woofer  
 (1) 1" (25mm) Silk Dome Tweeter  
**Cutout Dimensions:** 9-3/4" (197mm) Dia.  
**Finished Dimensions:**  
 10-3/4" Dia. x 4-3/4" D (271mm Dia. x 121mm D)  
**Weight:** 5 lbs. (2.27 kg)

## VM-815 In-ceiling 2-way Speaker



**Frequency Response:** 45Hz-20kHz (±3dB)  
**Sensitivity:** 90dB (2.83V @ 1 Meter)  
**Recommended Power:** 15-150 Watts  
**Drive Units:**  
 (1) 8" (203mm) Aluminum Cone Woofer  
 (1) 1" (25mm) Aluminum Dome Tweeter  
**Cutout Dimensions:** 9-3/4" (248mm) Dia.  
**Finished Dimensions:**  
 10-3/4" Dia. x 5" D (271mm Dia. x 127mm D)  
**Weight:** 6.15 lbs. (2.79 kg)

## VM-815L In-ceiling LCR Speaker



**Frequency Response:** 45Hz-20kHz (±3dB)  
**Sensitivity:** 90dB (2.83V @ 1 Meter)  
**Recommended Power:** 15-150 Watts  
**Drive Units:**  
 (1) 8" (203mm) Aluminum Cone Woofer  
 (1) 1" (25mm) Aluminum Dome Tweeter  
**Cutout Dimensions:** 10-1/4" (260mm) Dia.  
**Finished Dimensions:**  
 11-5/8" Dia. x 5-3/4" D (295mm Dia. x 146mm D)  
**Weight:** 5.95 lbs (2.70 kg)

**In-ceiling speaker grille options:  
 steel square white  
 (except the VM-815L);  
 stainless steel round  
 or square in  
 black or white.**