

MC Series

FREESTANDING SPEAKERS



REDEFINING THE WAY YOU EXPERIENCE SOUND.™

RBH Sound MC Series Freestanding Speakers

The MC Series speakers were designed for both the audio and home theater enthusiast, the MC Series features our proprietary aluminum cone technology; the very same technology you will find in our flagship products. Because of the inherent stiffness, low mass and self-damping properties found in aluminum, these advanced drivers deliver crisp, clear sound with the immediacy and accuracy needed to deliver the realism of today's high-definition music and movies. Computer optimized crossover networks in each speaker allow smooth integration between drivers while increasing power handling and minimizing distortion.

MC Series cabinets are constructed from medium density fiberboard (MDF) to effectively remove the cabinet from the sonic equation and leave only the drivers to create an immense soundstage with pinpoint imaging. Not to be outdone by the technology contained within, the cabinets are finished with the finest quality, genuine hardwood veneer.

Most people tend to leave the grilles on their speakers to hide the mechanics underneath. However, the Resonance Damping Alloy Baffle not only enhances the clarity of the speaker, but will tempt you to leave these grilles off and have your friends asking, "How much did you say you paid for these?"

We take the guessing game out of assembling the perfect home theater ensemble to match your needs. Each speaker within the MC Series is voice matched to provide a seamless integration between all speakers. No space for box speakers in the back of the room? No problem—we also offer MC Series in-wall loudspeakers that sonically match their freestanding counterparts.

High-quality components, great looks, and easy on the pocket-book — but most importantly, incredible sound is what RBH Sound and the MC Series is all about. Visit a dealer today and experience why, for over 27 years, RBH Sound has been redefining the way you experience sound.



MC-4C 2-Way Mini-bookshelf

Drive Units: (1) 4" (102mm) Woofer
(1) 1" (25mm) Tweeter
Power: 50-100 Watts
Sensitivity: 84dB (2.83V @ 1 Meter)
Impedance: 8 Ohms
Dimensions: 5¼" W x 8¾" H x 7¼" D
(133mm x 222mm x 184mm)
Frequency Response: 85Hz-20kHz ±3dB
Crossover Frequency: 3000Hz
Video Shielding: Standard
Weight: 7½ Lbs. (3.40 Kg)



MC-6C 2-Way Bookshelf

Drive Units: (1) 6½" (165mm) Woofer
(1) 1" (25mm) Tweeter
Power: 50-120 Watts
Sensitivity: 86dB (2.83V @ 1 Meter)
Impedance: 8 Ohms
Dimensions: 7¾" W x 12½" H x 8¾" D
(197mm x 318mm x 222mm)
Frequency Response: 60Hz-20kHz ±3dB
Crossover Frequency: 3000Hz
Video Shielding: Standard
Weight: 17 Lbs. (7.71 Kg)



MC-44C Surround

Drive Units: (2) 4" (102mm) Woofers
(2) 1" (25mm) Tweeters
Power: 50-150 Watts
Sensitivity: 87dB (2.83V @ 1 Meter)
Impedance: 6 Ohms
Dimensions: 10½" W x 9½" H x 6" D
(267mm x 241mm x 152mm)
Frequency Response: 30Hz - 180Hz ±3dB
Crossover Frequency: 40Hz - 180Hz
Video Shielding: Optional
Weight: 45 Lbs.



MC-414C 2-Way Center/RCR

Drive Units: (2) 4" (102mm) Woofers
(1) 1" (25mm) Tweeter
Power: 50-150 Watts
Sensitivity: 88dB (2.83V @ 1 Meter)
Impedance: 6 Ohms
Dimensions: 14½" W x 5¼" H x 7¼" D
(368mm x 133mm x 184mm)
Frequency Response: 85Hz-20kHz ±3dB
Crossover Frequency: 3000Hz
Video Shielding: Standard
Weight: 13 Lbs. (5.90 Kg)



MC-616C 2-Way Center/RCR

Drive Units: (2) 6½" (165mm) Woofers
(1) 1" (25mm) Tweeter
Power: 50-150 Watts
Sensitivity: 89dB (2.83V @ 1 Meter)
Impedance: 6 Ohms
Dimensions: 19½" W x 7¾" H x 9" D
(495mm x 197mm x 222mm)
Frequency Response: 50Hz-20kHz ±3dB
Crossover Frequency: 3000Hz
Video Shielding: Standard
Weight: 24 Lbs. (10.89 Kg)



TS-10A Subwoofer

Drive Units: (1)10" (254mm) Woofer
Power: 100-200 Watts RMS
Sensitivity: 87dB (2.83V @ 1 Meter)
Impedance: 4 Ohms
Dimensions: 14" W x 14¾" H x 17¾" D
(356mm x 375mm x 451mm)
Frequency Response: 30Hz-180Hz ±3dB
Crossover Frequency: 40Hz-180Hz (Variable)
Video Shielding: Optional
Weight: 45 Lbs. (20.41 Kg)



MC-6CT 2½-Way Tower

Drive Units: (3) 6½" (165mm) woofers
1" (25mm) tweeter
Power: 200 Watts
Sensitivity: 88dB (2.83V @ 1 Meter)
Impedance: 6 Ohms
Dimensions: 7¾" W x 40" H x 11½" D
(197mm x 1016mm x 292mm)
Frequency Response: 40Hz-20kHz ±3dB
Crossover Frequency: 100Hz, 3000Hz
Video Shielding: Standard
Weight: 55 Lbs. (24.95 Kg)



TS-12A Powered Subwoofer

Drive Units: (1) 12" (303mm) Woofer
Power: 100-200 Watts RMS
Sensitivity: 87dB (2.83V @ 1 Meter)
Impedance: 4 Ohms
Dimensions: 16" W x 18¾" H x 20¾" D
(406mm x 476mm x 514mm)
Frequency Response: 27Hz-200Hz ±3dB
Crossover Frequency: 40Hz-180Hz (Variable)
Video Shielding: Optional
Weight: 55 Lbs. (25.94 Kg)



RBH Sound • 382 Marshall Way, Layton, Utah • USA • 84041
Toll Free: (800) 543-2205 • Fax: (801) 543-3300 • www.rbhsound.com
It is RBH Sound policy to continuously incorporate improvements into products; all specifications are subject to change without notice. Copyright © 2011 RBH Sound. All Rights Reserved. 4/25/2011